

SPECIFICATIONS

Cooper SP350 Mobile Servicing Rig



Service Depth: 10,500 ft [3200.4 m]
(2-1/2" tubing)
Workover Depth: 8,500 ft [2590.8 m]
(2-7/8" DP)
Max. static hook load: 180,000 lbs (4 lines)
Clear Height: mast 96' [29.3 m]
Rated Horsepower: engine 350 hp / 2,200 rpm
Height: tubing board to ground 55 ft [16.8 m]
rod board to ground 78'-6" [23.9 m]
Carrier 4 axle-two steer and two drive axles
Diameter: wireline 1"
Road Traveling Dimensions: 56'-6" long x 9'-4"
wide x 13'-8" high 17.22 m long x 2.8 m wide x
4.2 m high
Carrier Dimensions: [excluding mast] 38' long x
9'4" wide x 9'-8" high 11.6 m long x 2.8 m wide x
2.9 m high
Maximum Speed: 55 mph [88.5 kmh]
Traveling Weight: 74,000 lbs [33566 kg] estimat-
ed (not including drill line, sand line, tools, block

Diesel Engine Specifications: Model Caterpillar C9 ACERT
Rated Horsepower: 350HP (2,200rpm)
Type: 6 cylinders straight line
Displacement: 8.8 L Diameter cylinder x stroke 112 mm x 149mm
Maximum Torque: 1,148 lb.ft (1,400rpm)
Compression Ratio: 16.1: 1
Rotation Direction: Counterclockwise (view from fly wheel)
Cooling Type: Water cooling



DRAGON

PRODUCTS, LTD.

1-877-235-8194

www.brucknertruck.com